


Product Sheet: Frame Cable

The SageGlass® Frame Cable connects the SageGlass insulating glass units (IGUs) to the control system. It can be ordered in a variety of lengths and conductor configurations to meet specific installation requirements. The plenum rated, PVC-insulated Frame Cable wires are 22 AWG.



Product Dimensions

Frame Cable is joined to the IGU pigtail with an easy-snap connector.



Part Numbers

Part Number	Cable Length	Conductors	Nominal Diameter	Wire Gauge
330-0140-001	15 m	2	5,6 mm	0,5 mm ²
330-0141-001		4	6,0 mm	
330-0140-002	23 m	2	5,6 mm	0,5 mm ²
330-0141-002		4	6,0 mm	
330-0140-003	38 m	2	5,6 mm	0,5 mm ²
330-0141-003		4	6,0 mm	

Temperature rated -20 to 70 °C

Product Ratings

Plenum rated



Installation

To protect the cable from damage while routing it through the framing system, use the grommets provided. A 3/8" (10mm) hole is required to install grommet. Frame Cables should be conditioned for 24 hours at room temperature prior to installation. The cables should never be installed below -20 °C ambient temperature. Once installed, the cables must not be exposed to sunlight, even through glass. If they are installed in an exposed location, they must be covered or painted (latex/water-based paint only). Non-adherence to these guidelines will void the warranty.

Parameter	2 Conductor Cable	4 Conductor Cable
Flame Retardant	IEC 60332-1-2	IEC 60332-1-2
Reaction to Fire (EN 50575)	B2 _{ca} -s1, d1, a1	B2 _{ca} -s1, d1, a1
Halogen Free	IEC 60754-1	IEC 60754-1
Non Corrosive Gas	IEC 60754-2	IEC 60754-2
Conductivity	≤ 10 μS/mm	≤ 10 μS/mm
pH Value	≥ 2.5	≥ 4.3
Non Dense Smoke	IEC 61034	IEC 61034
Max Pulling Tension	60 N	120 N
Min Bending Radius	28 mm	30 mm
Min Setting Radius	56 mm	60 mm
Nominal Resistance Conductor	34 Ω/km	34 Ω/km
Nominal Capacitance Conductor to Conductor @ 1kHz	90 pF/m	90 pF/m
Test Voltage Conductor to Conductor	2000 VDC	2000 VDC
Voltage Rating	300 V RMS	300 V RMS
Max Current per Conductor @ 25°C	3.75 A per conductor	3.75 A per conductor
Print	Saint-Gobain / Sage Glass - Belden Ye05081 Halogen Free 70c/-20c 2x0,5mm ² (Awg 20) Vdatecode + Metermarking	Saint-Gobain / Sage Glass - Belden Ye05082 Halogen Free 70c/-20c 4x0,5mm ² (Awg 20) Vdatecode + Metermarking

Conductor Count

Correct cable (2C or 4C) must be used per wiring/elevation diagram.

